

Carré Naval AVIFELT

14.09.2018

Carré Naval AVIFELT

Side: 1

Construction characteristics

Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	eTL	AVIFELT
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	eTL	Apr 5,5 mm.
Surface pile thickness	eTL	Apr 3,0 mm.
Tufts	eTL	Apr 166.700 pr.m2
Total carpet weight	ISO 8543	Apr 1.650 g/m2
Pile yarn weight	eTL	440 g/m2
Surface pile density	eTL	Apr 0,100 g/cm3
Soil protection	eTL	Yes

Performance characteristics

Performance areas	eTL	Class 33 - Commercial - Heavy
Suitability for use on stairs	eTL	Yes
Static control	eTL	Permanently antistatic
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	ISO 105-X12	>3
Colour fastness to rubbing dry	ISO 105-X12	>3-4
Colourfast. to water patterned	ISO 105-E01	>4
Colour fastness to water plain	ISO 105-E01	>3-4

Safety & Environment

Fire classification	eTL	Cfl-s1
	IMO	Certified
	USCG	164.117.EC0575/MEDB00003SD
	EC Type-Ex.Cert.No.	MEDB00003SD

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified

HAMMER
CARPETS

Hammer Tæpper A/S
Industrivej Syd 17-19, Birk
DK-7400 Herning
Tel +45 96 27 00 00
Fax +45 96 27 00 01
hammer@hammercarpets.com
www.hammercarpets.com

eTL = internal result from the ege Test Laboratory (ISO9001 certified).
Due to continuous development of products and testing procedures any above
declaration is subject to change without prior notification.