

Carré Naval Modular

3.02.2020

Carré Naval modular

Side: 1

Product description	Method	Product specifications
Construction characteristics		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	ETL	IMO 350
Dimensions	ISO 3018	48x48/96x96/24x96cm
Total thickness	ETL	Apr 6,5 mm.
Tufts	ISO 1763	Apr 183.000 pr.m2
Total carpet weight	ISO 8543	Apr 1.875 g/m2
	ISO 8543.	Apr 440 g/m2
Pile yarn weight	ETL	440 g/m2
Performance characteristics		
Static control	ETL	Permanently antistatic
Light reflectance	ETL	Testreport
Safety & Environment		
Fire classification	ETL	Cfl-s1
	IMO	Certified
	USCG	USCG164.117/EC0575/MEDB000046G
	EC Type-Ex.Cert.No.	MEDB000046G
Guides		
Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Manufacturer characteristics		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

HAMMER
CARPETS

Hammer Tæpper A/S
Industrivej Syd 17-19, Birk
DK-7400 Herning
Tel +45 96 27 00 00
Fax +45 96 27 00 01
hammer@hammercarpets.com
www.hammercarpets.com

eTL = internal result from the ege Test Laboratory (ISO9001 certified).
Due to continuous development of products and testing procedures any above
declaration is subject to change without prior notification.