

Product description	Method	Product specifications
<b>Construction characteristics</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	ETL	IMO 350
Dimensions	ISO 3018	48x48/96x96/24x96cm
Total thickness	ETL	Apr 6,5 mm.
Tufts	ISO 1763	Apr 183.000 pr.m2
Total carpet weight	ISO 8543	Apr 1.875 g/m2
	ISO 8543.	Apr 440 g/m2
Pile yarn weight	ETL	440 g/m2
<b>Performance characteristics</b>		
Static control	ETL	Permanently antistatic
Light reflectance	ETL	Testreport
<b>Safety &amp; Environment</b>		
Fire classification	ETL	Cfl-s1
	IMO	Certified
	USCG	USCG164.117/EC0575/MEDB000046G
	EC Type-Ex.Cert.No.	MEDB000046G
<b>Guides</b>		
Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
<b>Manufacturer characteristics</b>		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE